

# Arctic Cat DVX 400

Installation: Slip On & Full System



## Please Read Carefully

Read all instructions before installation. Make sure the vehicle and exhaust system are completely cool & on level ground before installation. You should have some mechanical knowledge and a basic set of tools. (A lift, center or rear stand will help.) We advise that this installation be done by a qualified technician. If this is a street vehicle, you may need to modify or replace your stock license plate bracket and turn signals. Please consult your local dealer. Check your local laws to make sure you are in compliance. HMF is not responsible if you are not.

## Stock Slip On Removal

1. Remove the **Thermostat Housing** located on the front of the motor. To do this, first put a **Drain Pan** under the **Thermostat Housing** with a hose going to the **Radiator**. *You may not need to do this on newer models the HMF Header can be installed.*
2. Remove the **Stock Head Pipe**.
3. Loosen the bolts on the **Header Port**.
4. Once loosened, support the **Exhaust** with one hand and remove.
5. Keep the **Stock Header Gasket**, you will need to reuse it.

## HMF Slip On Installation

1. Be sure the **Gasket** is placed flush into the Header Port.
2. Slide the **HMF Head Pipe** into the **Header Port** while aligning the **Flange** with the **Header Studs**.
3. Finger tighten the bolts onto the **Flange** so the **Head Pipe** can still be moved.
4. Slide the **T-Bolt Clamp** over the end of the **HMF Exhaust**, then slide the **Exhaust** onto the **Head Pipe**. *Some pushing and twisting may be necessary.*
5. Mount the **Exhaust** with supplied hardware and tighten.
6. Tighten the **Header Bolts** onto the **Flange** and **T-Bolt Clamp** to secure the **Exhaust** to the **Head Pipe**.
7. Reinstall the **Thermostat** and **Housing**, tighten the bolts, and top off your **Radiator**.
8. With most applications, re-jetting/remapping a **necessity**.

## Recommended Slip On Jetting Specifications:

**2003-2004:** 170 Main Jet **2005:** 145 Main Jet

These settings are to be used as a starting point and were determined on our dyno at 900ft - 60°F.

The final tuning is up to the customer. For more information about tuning, visit [www.HMFracing.com](http://www.HMFracing.com).

## Stock Full System Removal

1. Remove the **Thermostat Housing** located on the front of the motor. To do this, first put a **Drain Pan** under the **Thermostat Housing** with a hose going to the **Radiator**. *You may not need to do this on newer models the HMF Header can be installed.*
2. Remove the **Stock Head Pipe**.
3. Loosen the bolts on the **Header Port**.
4. Once loosened, support the **Exhaust** with one hand and remove.
5. Keep the **Stock Header Gasket**, you will need to reuse it.

## HMF Full System Installation

1. Be sure the **Gasket** is placed flush into the Header Port.
2. Slide the **HMF Head Pipe** into the **Header Port** while aligning the **Flange** with the **Header Studs**.
3. Finger tighten the bolts onto the **Flange** so the **Head Pipe** can still be moved.
4. Slide the **T-Bolt Clamp** over the end of the **HMF Exhaust**, then slide the **Exhaust** onto the **Head Pipe**. *Some pushing and twisting may be necessary.*
5. Mount the **Exhaust** with supplied hardware and tighten.
6. Tighten the **Header Bolts** onto the **Flange** and **T-Bolt Clamp** to secure the **Exhaust** to the **Head Pipe**.
7. Reinstall the **Thermostat** and **Housing**, tighten the bolts, and top off your **Radiator**.
8. With most applications, re-jetting/remapping a **necessity**.

## Recommended Full System Jetting Specifications:

**2003-2004:** 175 Main Jet **2005:** 150 Main Jet

These settings are to be used as a starting point and were determined on our dyno at 900ft - 60°F.

The final tuning is up to the customer. For more information about tuning, visit [www.HMFracing.com](http://www.HMFracing.com).

## Warranty Information

All HMF exhaust systems are covered by a limited warranty described on the enclosed warranty card. Mapping/Jetting and installation are the responsibility of the customer. HMF Performance exhausts are designed for closed-course competition use only.

## Having trouble? We can help.

If you're still having trouble with your installation, visit [www.HMFracing.com](http://www.HMFracing.com) and contact us by e-mail, Forums, or by calling 866.HMF.PIPE



This exhaust, EFI Controller, air filter, jet kit is not intended for use/sale in California and does not meet California, Federal, EPA, CARB noise or emission standards for on road/highway, public, private or state land and is prohibited for use by Federal law. This exhaust, EFI Controller, air filter, jet kit is intended for use in "closed course competition off road racing use only" on machines which do not fall under the California, Federal, EPA, CARB noise or emission standards. Modifications which exceed California, Federal, EPA, CARB noise or emission standards on non "Closed course competition off road racing use only" vehicles is prohibited by Federal law.

FOOTNOTE: 2006 and newer motorcycles with head/tail lights OEM from the manufacturer and every all terrain vehicle, even those intended for off road closed course competition use, are considered California, Federal, EPA CARB noise or emission controlled vehicles. Vehicle emission control information is noted in the owners manual and on the machine air box lid and exhaust muffler. Any modifications which exceed the California, Federal, EPA, and CARB noise or emission standard is prohibited by Federal LAW.