



Ducati Monster 696, 1100, & 1100S

Installation: Single & Dual Slip On System



Please Read Carefully

Read all instructions before installation. Make sure the vehicle and exhaust system are completely cool & on level ground before installation. You should have some mechanical knowledge and a basic set of tools. (A lift, center or rear stand will help.) We advise that this installation be done by a qualified technician. If this is a street vehicle, you may need to modify or replace your stock license plate bracket and turn signals. Please consult your local dealer. Check your local laws to make sure you are in compliance. HMF is not responsible if you are not.

Single Slip On System

Stock Single Slip On Removal

1. Make sure the motorcycle is on level ground and **completely** cooled down.
2. Remove the **Stock Silencer Springs** using a **Spring Puller** or **Piece of Wire**.
3. Loosen the **Stock Mounting Bolts**.
4. Remove the **Bolts** and **Silencer**.
5. Remove the **Two Clamps** and **Stock X Collector**. (You may need to loosen pipes at the Head)

HMF Single Slip On Installation

1. Slide the **T-Bolt Clamp** over the **HMF Y Collector** and install the **Collector**.
2. Slide the **HMF Silencer** over the **HMF Y Collector**.
3. Align and install the **Silencer Body Strap**.
4. Tighten the **Silencer Body Strap** and all **T-Bolt Clamps**.

Dual Slip On System

Dual Stock Slip On Removal

1. Make sure the motorcycle is on level ground and **completely** cooled down.
2. Remove the **Stock Silencer Springs** using a **Spring Puller** or **Piece of Wire**.
3. Loosen the **Stock Mounting Bolts**.
4. Remove the **Bolts** and **Silencer**.

HMF Dual Slip On Installation

1. Install the **External Mounting Brackets** using the supplied **Bolts**. **Do not tighten hardware**.
2. Slide the **HMF Silencers** onto the **Stock Head Pipe**.
3. Install the **Bolts**, align the **Silencers** and tighten all hardware.
4. Re-install the **Stock Springs**.

Warranty Information

All HMF exhaust systems are covered by a limited warranty described on the enclosed warranty card. Mapping/Jetting and installation are the responsibility of the customer. HMF Performance exhausts are designed for closed-course competition use only.

Having trouble? We can help.

If you're still having trouble with your installation, visit www.HMFracing.com and contact us by e-mail, Forums, or by calling 866.HMF.PIPE



This exhaust, EFI Controller, air filter, jet kit is not intended for use/sale in California and does not meet California, Federal, EPA, CARB noise or emission standards for on road/highway, public, private or state land and is prohibited for use by Federal law. This exhaust, EFI Controller, air filter, jet kit is intended for use in "closed course competition off road racing use only" on machines which do not fall under the California, Federal, EPA, CARB noise or emission standards. Modifications which exceed California, Federal, EPA, CARB noise or emission standards on non "Closed course competition off road racing use only" vehicles is prohibited by Federal law.
FOOTNOTE: 2006 and newer motorcycles with head/tail lights OEM from the manufacturer and every all terrain vehicle, even those intended for off road closed course competition use, are considered California, Federal, EPA CARB noise or emission controlled vehicles. Vehicle emission control information is noted in the owners manual and on the machine air box lid and exhaust muffler. Any modifications which exceed the California, Federal, EPA, and CARB noise or emission standard is prohibited by Federal LAW.