

Honda CRF 250 (04-05)

Installation: Slip On System



Please Read Carefully

Read all instructions before installation. Make sure the vehicle and exhaust system are completely cool & on level ground before installation. You should have some mechanical knowledge and a basic set of tools. (A lift, center or rear stand will help.) We advise that this installation be done by a qualified technician. If this is a street vehicle, you may need to modify or replace your stock license plate bracket and turn signals. Please consult your local dealer. Check your local laws to make sure you are in compliance. HMF is not responsible if you are not.

Stock Slip On Removal

- Remove the Right Side Panel. (See Figure 1)
- Loosen the Head Pipe to the Silencer Joint Clamp.
- Remove the upper and lower Silencer-to-Subframe Bolts and remove the Silencer. (See Figure 2)

HMF Slip On Installation

- Slide the T-Bolt Clamp into the S-bend Inlet.
- 2. Using the Stock Bolts, mount the HMF Silencer in the Stock location.
- Tighten the Silencer Mount Bolts, then tighten the T-Bolt Clamp. (See Figure 3) 3.
- Install the Right Side Panel.







Warranty Information

All HMF exhaust systems are covered by a limited warranty described on the enclosed warranty card. Mapping/Jetting and installation are the responsibility of the customer. HMF Performance exhausts are designed for closed-course competition use only.

Having trouble? We can help.

If you're still having trouble with your installation, visit www.HMFracing.com and contact us by e-mail, Forums, or by calling 866.HMF.PIPE





866.HMF.PIPE



for use by Federal law. This exhaust, EFI Controller, air filter, jet kit is intended for use in "closed course competition off road racing use only" on machines which do not fall under the California, Federal, EPA, CARB noise or emission ARB noise or emission standards on non "Closed course competition off road racing use only" vehicles is prohibited by Federal law.