



Polaris RZR 170

Installation: Slip On System



Please Read Carefully

Read all instructions before installation. Make sure the vehicle and exhaust system are completely cool & on level ground before installation. You should have some mechanical knowledge and a basic set of tools. (A lift, center or rear stand will help.) We advise that this installation be done by a qualified technician. If this is a street vehicle, you may need to modify or replace your stock license plate bracket and turn signals. Please consult your local dealer. Check your local laws to make sure you are in compliance. HMF is not responsible if you are not.

Stock Slip On Removal

1. Make sure the machine is on level ground and **completely** cooled down.
2. Loosen the **Silencer Mounting Bolts**.
3. Remove the two bolts from the **Exhaust Port**.
4. Brace the back of the **Silencer** with one hand, and take the bolts the rest of the way out.
5. Pull back and twist until the **Silencer** is removed.
6. Inspect the **Stock Head Pipe Gaskets**. If they're damaged, replace them.

HMF Slip On Installation

1. Slide the **Stock Gasket** onto the **HMF Head Pipe**.
2. Slide the **T-Bolt Clamp** over the end of the **HMF Silencer**, then slide the **Silencer** onto the **Head Pipe**. Some pushing and twisting may be necessary.
3. Mount the **Silencer** with the supplied hardware and tighten all hardware.
4. Tighten the **T-Bolt Clamp** to secure the exhaust to the **Head Pipe**.
5. With most applications, remapping is a necessity.

Warranty Information

All HMF exhaust systems are covered by a limited warranty described on the enclosed warranty card. Mapping/Jetting and installation are the responsibility of the customer. HMF Performance exhausts are designed for closed-course competition use only.

Having trouble? We can help.

If you're still having trouble with your installation, visit www.HMFracing.com and contact us by e-mail, Forums, or by calling 866.HMF.PIPE



This exhaust, EFI Controller, air filter, jet kit is not intended for use/sale in California and does not meet California, Federal, EPA, CARB noise or emission standards for on road/highway, public, private or state land and is prohibited for use by Federal law. This exhaust, EFI Controller, air filter, jet kit is intended for use in "closed course competition off road racing use only" on machines which do not fall under the California, Federal, EPA, CARB noise or emission standards. Modifications which exceed California, Federal, EPA, CARB noise or emission standards on non "Closed course competition off road racing use only" vehicles is prohibited by Federal law.
FOOTNOTE: 2006 and newer motorcycles with head/tail lights OEM from the manufacturer and every all terrain vehicle, even those intended for off road closed course competition use, are considered California, Federal, EPA CARB noise or emission controlled vehicles. Vehicle emission control information is noted in the owners manual and on the machine air box lid and exhaust muffler. Any modifications which exceed the California, Federal, EPA, and CARB noise or emission standard is prohibited by Federal LAW.